

Layer 3 Unicast Routing Configuration

This chapter describes the configuration steps of Layer 3 routing, including static routing, RIPv2, OSPFv2, VRRP, and ECMP.

- Layer 3 VLAN Interface Configuration
- ARP Configuration
 - Configuring ARP
 - Dynamic ARP Inspection (DAI)
 - Flushing ARP and the Neighbor Table
- Configuring IP Routing
- VRF Configuration Guide
 - Introduction to VRF
 - Configuration Notes of VRF
 - Configuring a User-defined VRF
 - Enabling Management VRF
 - Example for Configuring Basic VRF
- DHCP Configuration
 - Introduction to DHCP
 - Configuration Notes of DHCP
 - Configuring DHCP Server
 - Configuring DHCP Relay
 - Configuring DHCP Snooping
 - Typical Configuration Example for DHCP Relay and DHCP Snooping
 - RFC Lists
- Default Administrative Distance Values
- Static Routing Configuration
- Static Routing Configuration Example
- RIPv2 Routing Protocol Configuration
- RIPv2 Routing Configuration Example
- OSPF (Open Shortest Path First)
 - OSPF Overview
 - Basic OSPF Configuration Tasks
 - Basic OSPF Configuration Example
 - OSPFv3 Routing Protocol Configuration
 - OSPF Configuration Example: NSSA Stub Normal
 - OSPF Stub Area NSSA Summary
 - OSPF Virtual Link Configuration Guide
 - OSPF Area Range Configuration Guide
 - OSPF Route Import and Export
 - Overview
 - Configuring OSPF Route Import and Export
 - Example for Configuring OSPF Introducing Route by Using Export
 - Example for Configuring OSPF Import and Export
 - Example for Configuring OSPF with Different VRFs
- BFD Protocol Configuration
- BFD Basic Configuration Example
- ECMP (Equal-Cost Multipath Routing) Configuration
- Symmetric Hash for ECMP Configuration Example
- VRRP Configuration
 - Principle of VRRP
 - Configuration Notes of VRRP
 - Configuring Standard VRRP
 - Configuring Active-Active VRRP
 - VRRP Configuration Example
 - Example for Configuring Standard VRRPv3 for IPv4
 - Example for Configuring Active-Active VRRPv3 for IPv4
 - Example for Configuring Active-Active VRRPv3 for IPv6
- IPv6 Neighbor Configuration
- IPv6 Static Routing Configuration
- IPv4/IPv6 BGP Configuration
 - IPv4 BGP configuration
 - BGP Configuration Guide
 - BGP Basic Configuration Example
 - BGP Route Reflector Configuration Example
 - BGP Confederation Configuration Example
 - BGP Load Balancing Configuration Example
 - IPv6 BGP Configuration
 - IPv6 BGP Introduction
 - Building Peering Sessions
 - EBGP Peering
 - IBGP Peering
 - Establish BGP Peer Use 4-byte-AS-Number
 - Sources of Routing Updates
 - Injecting Information Dynamically into BGP
 - Injecting Information Statically into BGP
 - BGP Attributes
 - The NEXT_HOP Attribute

- The AS_PATH Attribute
 - The LOCAL_PREF Attribute
 - The MULTI_EXIT_DISC Attribute
 - The COMMUNITY Attribute
 - BGP-4 Aggregation
 - Synchronization
 - Controlling Large-Scale Autonomous System
 - Confederations
 - Route Reflectors
 - Redundancy and Load Balancing
 - Designing Stable Internets
- Label BGP
 - Labeled BGP Support
 - Configuration Example for Labeled Support
 - IPV4 Labeled BGP Configuration
 - IPV6 Labeled-BGP Configuration
 - Debugging CLI for Labeled-BGP
- IPv6 RA Guard Configuration